

## ***FALCO 600 with VFD controlled 15hp dilution blower***



The FALCO 600 with dilution blower and variable frequency drive is the ideal solution for industrial vapor treatment. Process vapors are captured and efficiently destroyed by catalytic oxidation.

Startup and operation are fully automatic. Temperature controllers accurately regulate inlet concentrations by adjusting dilution blower speed. Speed is increased during high mass flow of hydrocarbon and slows during low mass flow or at standby to save energy. Automatic shutdown results if temperatures exceed limits. The FALCO 600 has an efficient spiral plate heat exchanger. A bypass valve automatically increases heat recovery during low concentration operation and standby, and reduces heat recovery to accommodate high concentrations.

The FALCO 600 has a massive catalyst volume for its rated capacity, providing longer life and poison resistance than monolith type catalysts.

Components are mounted on stainless steel frames which support the FALCO 600, blower, VFD, and accessories. This low profile system weighs only 2,500 lb. and is 50" wide, 78" long, and 87" tall. This standardized package is easily installed and operated and can be integrated into a wide range of process air streams.

### **Packaged system includes the following:**

- FALCO 600 Catalytic Oxidizer
- 15 hp, three phase, explosion proof, inverter duty, regenerative blower
- Square D variable frequency drive in ventilated NEMA 3R enclosure
- Solberg inline process air and 4" dilution air filter
- Stainless steel vacuum and pressure gauges
- Mounting frames, factory piping and wiring between FALCO, Blower, and VFD
- Factory Mutual approval for use in Class 1, Division 2, Group D Hazardous Locations



### **FALCO 600 specifications:**

- Capacity 300-700 scfm (dilution air + process flow)
- Maximum input loading 0.3 lb/min VOCs @ 19,000 BTU/lb (5668 BTU/min)
- Destruction Efficiency Up to 99.5%
- Catalyst operation range (standard) 330-620°C (626-1148°F)
- Catalyst Packed bed 4.9 cubic feet. Platinum and Palladium on 1/8" ceramic beads is standard. Alternate catalysts are available
- Heat exchanger Stainless steel spiral plate. 73% efficient at 300 scfm.
- Heater (Electric Solid State Control) 75 amp @ 208 V (27 kW), 86.7 amp @ 240 V (36 kW) or, 43 amp @ 480 V (36 kW)  
Canada: 69 amp @ 208 V (24.7 kW), 79.4 amp @ 240 V (33kW)  
40 amp @ 480 V (33 kW)
- Construction 304 stainless steel heat exchanger and vessel  
Stainless steel frame, stainless steel piping
- Power requirements Heater and Blower: 3 phase 480V, *Optional* 3 phase 208-240 V  
Controls: 120 V

# **FALCO**

**FALMOUTH PRODUCTS P.O. BOX 541 FALMOUTH, MA 02541**

**Phone 508 548 6686 [www.falmouthproducts.com](http://www.falmouthproducts.com)**

[sales@falmouthproducts.com](mailto:sales@falmouthproducts.com)

**Rev 11-10-17**