



PI = PRESSURE INDICATOR  
 PSL = PRESSURE SWITCH, LOW (LOW INLET FLOW)  
 TT = TEMPERATURE TRANSMITTER  
 VFD = VARIABLE FREQUENCY DRIVE  
 FA = FLAME ARRESTOR  
 CATOX = CATALYTIC OXIDIZER  
 HBV = HEAT EXCHANGER BYPASS VALVE  
 FM = FLOW METER (PITOT TUBE)  
 DPT = DIFFERENTIAL PRESSURE TRANSMITTER  
 E-STOP = DILUTION BLOWER EMERGENCY STOP SWITCH

TT1 = CATALYST INLET TEMPERATURE  
 TT2 = CATALYST EXIT TEMPERATURE  
 TT3 = CATALYST INTERNAL TEMPERATURE

\* OPTIONAL DEVICE, MAY NOT BE PRESENT  
 \*\* CRITICAL SAFETY DEVICE

FALMOUTH PRODUCTS  
 530 THOMAS LANDERS RD  
 FALMOUTH, MA 02574  
 PHONE: 508-548-6686  
 FAX: 508-548-8144

**FALMOUTH PRODUCTS**

FALCO 300 - P&ID  
 WITH VARIABLE  
 FREQ. DRIVE

	NAME	DATE
DRAWN	MW	11/6/13
CHECKED		

SIZE	DWG. NO.	REV.
A	5090	E
SCALE: 1:1	WEIGHT:	SHEET 1 OF 1