

FALCO 300 with Optional 10 hp Blower Package



The blower package combines with the FALCO 300 to form an integrated vapor extraction and treatment system. Factory assembly minimizes work on site.

Components are mounted on frames joined by forklift beams. One frame supports the blower, Vapor Control Valve, and accessories. The second frame supports the FALCO 300. This low-profile system weighs 1,425 lbs and is 4' wide, 5' 7" long, and 6' 2" tall. It fits in a parking space or a full-size pickup truck.

When integrated with the FALCO 300, this 10 hp blower provides the following performance:

25" H ₂ O vacuum	=	292 scfm oxidizer flow
40" H ₂ O vacuum	=	268 scfm oxidizer flow
70" H ₂ O vacuum	=	206 scfm oxidizer flow

System is fully wired and tested at Falmouth Products for maximum reliability and continuous outdoor operation. This unit can be installed and running in less than three hours with one conduit to your breaker box and one connection to the vapor source. Entire system is Third Party approved for use in hazardous locations.

Packaged system includes the following:

- FALCO 300 Catalytic Oxidizer
- Gast 10 hp, three phase, explosion proof, regenerative blower model # R7100R-50
- FALCO Vapor Control Valve (VCV) with filter
- Solberg 3" inline blower filter
- Stainless steel vacuum and pressure gauges
- Vacuum relief valve
- Recirculation valve for flow adjustment
- Stainless steel mounting rails with forklift pockets
- Mounting frames, factory piping and wiring between FALCO, blower and VCV



FALMOUTH PRODUCTS – A division of Product Recovery Management, Inc.
200 20th Street, Butner, NC, 27509
Phone 508 548 6686 www.falmouthproducts.com
sales@falmouthproducts.com